

Your Versatile Partner



TX-5200E



TX-5200

## TX-5200/5200E

### Powerful Fanless POS Box

The TX-5200 Series is the enhanced version of the TX-5000 Series. The latest high-end fanless POS Box now has USB 3.0 x 5 ports, incorporating leading CPU technology - 4<sup>th</sup> generation Intel Haswell processor; the TX-5200 Series provides unmatched performance while juggling multiple programs with ease.

# TX-5200/5200E

## High Performance

With SSD and the 4<sup>th</sup> generation Intel Haswell processor up to Core i7, the TX-5200 Series is faster, cooler and more efficient. With the patented fanless design, it delivers unparalleled performance at completely silent operation.

## Compact and Hassle-free

Its small footprint allows the device to be placed anywhere you need a Point of Service system. Built-in PoweredUSB ports free up the need for multiple power adapters for peripherals and keep the counter neat and tidy.

## Expandable and Flexible

Connect to a wide range of POS peripheral options for greater productivity and flexibility. Additional HDMI port allows the TX-5200 Series to function as a high-end digital signage player.

Specification	TX-5200	TX-5200E
Processor	Intel Haswell Core i5-4570TE CPU, up to 3.30 GHz, 4M Cache; Intel Haswell Core i7-4770TE CPU, up to 3.30 GHz, 8M Cache	
System Memory	DDR3L SO-DIMM x 2, max. 16GB	
Storage Device	SATA Storage x 2, factory default SSD x 1	
RAID Function	Yes, optional 2nd SSD required	
Intel vPro Support	Yes	
Power Supply	12V/80W	12V/150W
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request	

## I/O & Expansion

Serial Port	6, DB9 x 4, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports	
Parallel Port	1	
Standard USB Port	8, USB 3.0 x 5 + USB 2.0 x 3	5, USB 3.0 x 5
PoweredUSB Port	N/A	3, 24V x 1 + 12V x 2
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support for Posiflex monitors; HDMI x 1	
CR Port	1, control 2 CR via optional Y-cable	
Audio	Internal 2W speaker x 1 (optional) + Mic-in/Line-out	
Expansion Slot	Mini PCIe slot x 1	

## Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 83
Weight (N. W. in kg)	2.75

## Environmental

Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

## Option

Built-in WiFi	Mini-PCIe WiFi/BT module
---------------	--------------------------

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\*The product information and specifications are subject to change without prior notice.

Certifications	      	EN201712V2
----------------	--	------------

**POSIFLEX**

### POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan  
 Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw  
 Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller