

ForPOS

VI 650 LCD UPS Specification

Key Features

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11 surge protection
- Monitoring software included
- LCD display for status view



Product Features		Connections	
Capacity	650VA/360W	Communications	USB
Input		Outlets	2x UK and 1 x IEC
Voltage	220/230/240VAC	Surge Protection	RJ-11 (in/out)
Voltage Range	160-290VAC	Software & System Requirements	
Output		Software	ViewPower
Voltage	220/230/240VAC	Operating System	For details visit: www.forpos.co.uk
Voltage Regulation (Battery Mode)	± 10%	Other	1x USB port
Frequency	50Hz or 60Hz	Product Details	
Frequency Regulation (Battery Mode)	± 1Hz (Battery Mode)	Dimensions	287 x 100 x 142 mm
Waveform	Simulated Sine Wave	Colour	Black
Battery		Weight	4.3 kg
Type	12V / 7Ah	Model Code	PWUPS-650-LED
Quantity	1x	Environment	
Recharge Time	4h for 90%	Temperature	0°C – 40°C
Transfer Time		Humidity	0% - 90% RH (non-condensing)
Typical	2-6 ms	Audio Indicators	
LCD Display		Battery Mode	Beep every 4 sec
Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm, and Low battery alarm	Low Battery	Beep every second
		Fault	Continuous Beep
		Battery Weak	Beep every 2 sec
		Battery Fault	Beep (x3 interval)
Full Protection			
Discharge Prevention	Yes		
Deep Discharger	Yes		
Overcharge	Yes		
Overload	Yes		



ForPOS Ltd
 Unit G4, Kingston Business Park
 Kingston Bagpuize
 Oxford
 OX13 5FE
 T: +44 (0) 1865 820 925
 E: info@forpos.co.uk
 W: www.forpos.co.uk