



Simplicity is the
Ultimate Sophistication

Cachet JK-3200 Series

32" Modular Kiosk



HIGHLIGHTS

- 32" true-flat PCAP touch screen
- Flexible configurations:
single / dual sided floor-standing, wall-mount
- Modular design for easy serviceability
- Popular uses: product display & advertising, ordering & payment, click & collect, ticketing & e-reservations, wayfinding & customer guidance



Windows/Android



NFC/RFID reader



2D scanner



Fingerprint sensor



Status Indicator



EMV Supportive*



PRODUCT SHOWCASE / Cachet JK-3200 Series



| Specifications | | JK-3210 | JK-3230 | JK-3250 |
|---------------------|------------------------------------|---|--|---|
| Computer | Processor | Dual Cortex-A72 + Quad Cortex-A53 | Intel Bay Trail J1900 Quad Core, up to 2.42 GHz, 2M Cache | Intel 7th Generation Kaby Lake U Core i3/i5 |
| | System Memory | DDR4, 2GB | DDR3L SO-DIMM slot x 1, max. 8 GB | DDR4 SO-DIMM slot x 1, max. 16 GB |
| | Storage Device | 16 GB eMMC | SATA SSD x 1 | |
| | Intel vPro Support | N/A | N/A | Core i3: N/A Core i5: Yes (for option) |
| | TPM Support | N/A | Yes (for option) | |
| | Power Supply | 12V/60W x 1+ 24V/60W x 1 | 12V/60W x 1 + 24V/60W x 1 | |
| | OS Support | Android 9.0 | Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT | Windows 10 IoT 64 bit |
| | Serial Port | RJ50 x 2 | 3, RJ50 x 2 + DB9 x 1 | |
| | Standard USB Port | 6, USB 3.0 x 1 + USB 2.0 x 5 | 8, USB 3.0 x 1 + USB 2.0 x 7 | 8, USB 3.0 x 2 + USB 2.0 x 6 |
| | OTG USB | 1, micro USB x 1 | N/A | |
| | Display Port | HDMI x 1 | HDMI x 1 | |
| | LAN Port | 10/100/1000 Mb x 2 | 10/100/1000 Mb x 2 | |
| | Audio | Internal 3W speaker x 2 | Internal 3W speaker x 2 | |
| | Internal Expansion Slot | N/A | M.2 x 1 | |
| Display & Touch | LCD | 32" | | |
| | Resolution | 1920 x 1080 | | |
| | Touch | True-flat PCAP touch with multi-touch support | | |
| Physical Dimension | Dimension (W x D x H in mm) | 495 x 150 x 1934 (with pole) 495 x 180 x 1934 (with wall mount bracket) | | |
| | Weight (N. W. in kg) | 65 (with pole) 35 (with wall mount bracket) | | |
| Environmental | Operating Condition | 0°C - 40°C, 20%RH - 90%RH | 0°C - 40°C, 20%RH - 90%RH (Equipped with SSD) | |
| | Storage Condition | -20°C - 70°C, 10%RH - 90%RH | | |
| Standard Components | Status Indicator | RGB Color LED indicator | | |
| | Proximity Sensor | Range from 60 cm to 100 cm | | |
| | Camera | 1MP wide angle camera | | |
| | Printer | 3" thermal printer w/ auto cutter, 200 mm/sec (max.) | | |
| Optional Components | WiFi | USB dongle | M.2 WiFi/BT module | |
| | Scanner | 2D barcode scanner | | |
| | EMV Payment Device Bracket Support | Custom bracket support for various EMV payment devices | | |
| | MSR | 3 tracks ISO or JISII (HID/VCOM selection) | | |
| | Fingerprint Sensor | Optical type | | |
| | NFC/RFID Reader | N/A | Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18092) | |
| | 4G LTE | Support selected bands & countries with full SIM slot (mini-PCIe module) by request | | |

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc. *Posiflex does not sell the EMV payment devices, but can provide bracket support with an additional charge. *The product information and specifications are subject to change without prior notice.



POSIFLEX TECHNOLOGY, INC.
 No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
 Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
 Fax : +886-2-2268-5388 www.posiflex.com



Authorized Distributor / Reseller