

PC-2111E-G2



Specification	PC-2111E-G2
Processor	Intel Elkhart Lake Celeron J6412
System Memory	1x DDR4 SO DIMM, max. 16GB
Storage Device	1 x M.2 2280
TPM	TPM 2.0
Power Supply	12V/60W
OS Support	Windows 10 IoT 64 bit Windows 11 IoT GAC

Display & Touch

LCD	10.1" TFT LCD with LED backlight
Resolution	1280 x 800
Touch	PCAP supporting multi-touch

I/O & Expansion

Serial Port	RJ-50 x 1
Standard USB Port	4 x USB 3.0
LAN Port	1 x 10 / 100 / 1000 Mb
Display Port	1 x mini-HDMI
CR Port	1, control 2 x CR, support 24V
Audio	1 x internal speaker
LED Indicator	1 x bi-color LED
Expansion Slot	1 x M.2 2230 for WiFi/BT

Physical Dimension

Dimension (W x H x D in mm)	259 x 192.8 x 200.7
Weight (N. W. in kg)	1.96kg (With base stand)

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Attachment Options

Attachment	TA-220
Base	N/A

Extraordinary Within



PC-2111E-G2

10.1" Panel PC

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications



EN20240220V3



POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller