

# *POSIFLEX*

TX-5000E



TX-5000

Your Versatile Partner

## TX-5000/5000E

### Powerful Fan-free POS Box

TX-5000 Series is the latest high-end fan-free POS Box. Incorporating leading CPU technology - 4th generation Intel® Haswell processor, TX-5000 Series provides unmatched performance while juggling multiple programs with ease.

# TX-5000/5000E

## High Performance

With SSD and the 4th generation Intel Haswell processor up to Core i7, TX-5000 Series is faster, cooler and more efficient. In conjunction with patented fan-free technology, it delivers the unparalleled performance at completely silent operation.

## Compact and Hassle-free

Small footprint design allows this POS box to be placed anywhere you need a Point of Service system. Built-in PoweredUSB ports free up the need for multiple power adapters for peripherals and keep the counter neat and tidy.

## Expandable and Flexible

Connect to a wide range of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

System Configuration	TX-5000	TX-5000E
Processor	Intel G1820/2.7GHz/2M Cache Intel G3320TE/2.3GHz/3M Cache Intel Core i3-4330TE/2.4GHz/4M Cache Intel Core i5-4570TE/2.7GHz up to 3.3GHz/4M Cache Intel Core i7-4770TE/2.3GHz up to 3.3GHz/8M Cache	
System Memory	DDR3 1333 SO-DIMM x 2, max. 16GB (DDR3 1333/1600 for Core i3 and above CPU)	
Storage Device	SATA Storage x 2, factory default 32GB SSD x 1	
RAID	N/A	
Power Supply	12V/80W	12V/150W
OS support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Linux per request	
<b>Connectivity</b>		
Serial Port	6, DB9 x 4, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports	
Parallel Port	1	
Standard USB Port	8 (USB 3.0/2.0 x 2 + USB2.0 x 6)	5 (USB 3.0/2.0 x 2 + USB 2.0 x 3)
PoweredUSB Port	N/A	24V x 1 + 12V x 2
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support for Posiflex monitors; DP x 1	
CR Port	1, control 2 CR via optional Y-cable	
PS/2 Port	N/A	
UPS Port	N/A	
Audio	Internal 2W speaker x 1 (optional) + Mic-in/Line-out	
Internal Expansion Slot	mini-PCIe slot x 1	
<b>Built-in Device</b>		
Built-in WIFI	Optional mini-PCIe WIFI module	
<b>Physical Dimension</b>		
Dimension (W x D x H in mm)	220 x 202 x 83	
Weight (N. W. in kg)	2.75	
<b>Environmental</b>		
Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	

### Certifications



ORACLE

Design and Manufacturing in Taiwan by Posiflex Technology Inc.  
The product information and specifications are subject to change without prior notice.

2015Q1



POSIFLEX TECHNOLOGY INC.  
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan  
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw  
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller